




POLLUX SUSPENSION

by Jan Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIMENSIONS		LIGHTSOURCE	FINISH	TYPE.NR	
L	205 cm80.7 inch	886x led 12V/0.6W, 2800K, 26580 LM, CRI>95	Nickel	11-9200	
H	187 cm73.6 inch		Brass	11-9200-2	
W	105 cm41.3 inch		Blackbrass	11-9200-4	
CANOPY		INCLUDED			
L	59.5 cm23.4 inch		Yes		
H	10 cm3.9 inch				
W	37 cm14.6 inch				
CABLELENGTH					
Up to 200 cm78 inch					

TYPE	Suspension
STANDARD	
OPTIONAL	2400K.
TRANSFORMER/DRIVER	Meanwell HLG600
DIMMING	0-10V
CLASSIFICATION	UL no IP20 yes
ENERGY LABEL	

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands

T. +31-(0)183-447887

info@quasar.nl www.quasar.nl