Product data sheet

Date: May 6th 2024

QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIMENSIONS		
L	179 cm 70.5 inch	
Н	108 cm 42.5 inch	
W	105 cm 41.3 inch	
CANOPY		

L 59.5 cm 23.4 inch 10 cm 3.9 inch Н W 37 cm 14.6 inch

CABLELENGTH Up to 200 cm 78 inch 464x led 12V/0.6W. 2800K, 13920 LM, CRI>95

INCLUDED Yes





TYPE.NR 11-9201 11-9201-2 11-9201-4

TYPE	Suspension
STANDARD	
OPTIONAL	2400K.
TRANSFORMER/DRIVER	Meanwell HLG600
DIMMING	0-10V
CLASSIFICATION	UL no IP20 yes
ENERGY LABEL	
YEAR OF DESIGN	2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 info@quasar.nl www.quasar.nl