

# Product data sheet

Date: September 8th 2024


# QUASAR



## POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



### DIMENSIONS

L 125 cm 49.2 inch  
H 200 cm 78.7 inch  
W 75 cm 29.5 inch

### CANOPY

L 59.5 cm 23.4 inch  
H 10 cm 3.9 inch  
W 37 cm 14.6 inch

### CABLELENGTH

Up to 200 cm 78 inch

### LIGHTSOURCE

717x led, 12V/0.6W,  
2800K, 21510 LM, CRI>95

### INCLUDED

Yes



### FINISH

Nickel  11-9203-1  
Brass  11-9203-2  
Blackbrass  11-9203-4

### TYPE.NR

TYPE	Suspension
STANDARD	
OPTIONAL	2400K.
TRANSFORMER/DRIVER	Meanwell HLG601
DIMMING	0-10V
CLASSIFICATION	UL no IP20 yes
ENERGY LABEL	
YEAR OF DESIGN	2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands

T. +31-(0)183-447887

info@quasar.nl www.quasar.nl