Product data sheet

Date: November 23rd 2024






POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



60 cm 23.6 inch 120 cm 47.2 inch W 60 cm 23.6 inch

CANOPY

25 cm 9.8 inch 6 cm 2.4 inch 25 cm 9.8 inch

CABLELENGTH Up to 200 cm 78 inch

232x led. 12V/0.6W. 2800K, 12630 LM, CRI>95

INCLUDED

Yes

KG KG

FINISH Nickel

TYPE.NR 11-9206-1 11-9206-2 Blackbrass 11-9206-4

20 65x125x65cm

TYPE Suspension

STANDARD

2400K. OPTIONAL

TRANSFORMER/DRIVER Meanwell HLG604

DIMMING 0-10V

UL no CLASSIFICATION

IP20 yes

ENERGY LABEL

YEAR OF DESIGN 2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 info@quasar.nl www.quasar.nl