Product data sheet

Date: January 2nd 2025


QUASAR




POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.







205 cm80.7 inch 187 cm 73.6 inch W 105 cm 41.3 inch

CANOPY

59.5 cm 23.4 inch 10 cm 3.9 inch W 37 cm 14.6 inch

CABLELENGTH Up to 200 cm 78 inch

886x led 12V/0.6W. 2800K, 26580 LM, CRI>95

INCLUDED



TYPE.NR 11-9200 Nickel

11-9200-2 Blackbrass 11-9200-4

TYPE Suspension

STANDARD

2400K. OPTIONAL

TRANSFORMER/DRIVER Meanwell HLG600

DIMMING 0-10V

UL no CLASSIFICATION IP20 yes

ENERGY LABEL

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. + 31 - (0)183 - 447887 info@quasar.nl www.quasar.nl