

Product data sheet

Date: January 2nd 2025


QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIMENSIONS

L 256 cm 100.8 inch
H 85 cm 33.5 inch
W 105 cm 41.3 inch

CANOPY

L 59.5 cm 23.4 inch
H 10 cm 3.9 inch
W 37 cm 14.6 inch

CABLELENGTH

Up to 200 cm 78 inch

LIGHTSOURCE

545x led 12V/0.6W,
2800K, 16350 LM, CRI>95

INCLUDED

Yes



FINISH

Nickel ● 11-9202
Brass ● 11-9202-2
Blackbrass ● 11-9202-4

TYPE.NR

TYPE	Suspension
STANDARD	
OPTIONAL	2400K.
TRANSFORMER/DRIVER	Meanwell HLG600
DIMMING	0-10V
CLASSIFICATION	UL no IP20 yes
ENERGY LABEL	
YEAR OF DESIGN	2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands

T. +31-(0)183-447887

info@quasar.nl www.quasar.nl