Product data sheet

Date: March 12th 2025

QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIMENSIONS		
L	280 cm110.2 inch	
Н	125 cm 49.2 inch	
W	130 cm 51.2 inch	
CAI	CANOPY	
L	59.5 cm 23.4 inch	

10 cm 3.9 inch Н W 37 cm 14.6 inch

CABLELENGTH Up to 200 cm 78 inch 1017x led. 12V/0.6W. 2800K, 30510 LM, CRI>95

INCLUDED Yes





TYPE.NR 11-9204-1 11-9204-2 11-9204-4

TYPE	Suspension	
STANDARD		
OPTIONAL	2400K.	
TRANSFORMER/DRIVER	Meanwell HLG602	
DIMMING	0-10V	
CLASSIFICATION	UL no IP20 yes	
ENERGY LABEL		
YEAR OF DESIGN	2019	

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 info@quasar.nl www.quasar.nl