Product data sheet

Date: August 31st 2025


QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



179 cm 70.5 inch 108 cm 42.5 inch W 105 cm 41.3 inch

CANOPY

59.5 cm 23.4 inch 10 cm 3.9 inch 37 cm 14.6 inch

CABLELENGTH Up to 200 cm 78 inch

464x led 12V/0.6W. 2800K, 13920 LM, CRI>95

INCLUDED

Yes

KG KG 150 189x118x130cm FINISH

Nickel

TYPE.NR 11-9201 11-9201-2 Blackbrass 11-9201-4

TYPE

Suspension

STANDARD

OPTIONAL

2400K.

TRANSFORMER/DRIVER

DIMMING

CLASSIFICATION

UL IP20

ENERGY LABEL

YEAR OF DESIGN 2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887

> info@quasar.nl www.quasar.nl