Product data sheet

Date: August 31st 2025

QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIMENSIONS	LIGHTSOURCE	FINISH	TYPE.NR
L 280 cm110.2 inch	1017x led, 12V/0.6W,	Nickel	11-9204-1
H 125 cm 49.2 inch	2800K, 30510 LM, CRI>95	Brass	11-9204-2
W 130 cm 51.2 inch		Blackbrass	11-9204-4
	INCLUDED	•	
CANOPY	Yes		
L 59.5 cm 23.4 inch			
H 10 cm 3.9 inch			
W 37 cm 14.6 inch	KG		
	15 200 290x140x150cm		
CABLELENGTH			
Up to 200 cm 78 inch			

TYPE	Suspension
STANDARD	
OPTIONAL	2400K.
TRANSFORMER/DRIVER	
DIMMING	
CLASSIFICATION	UL IP20
ENERGY LABEL	
YEAR OF DESIGN	2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 info@quasar.nl www.quasar.nl