Product data sheet

Date: April 19th 2025


QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



60 cm 23.6 inch 120 cm 47.2 inch W 60 cm 23.6 inch

CANOPY

25 cm 9.8 inch 6 cm 2.4 inch 25 cm 9.8 inch

CABLELENGTH Up to 200 cm 78 inch

232x led. 12V/0.6W. 2800K, 12630 LM, CRI>95

INCLUDED

Yes

KG KG 20 65x125x65cm FINISH

Nickel

TYPE.NR 11-9206-1 11-9206-2 Blackbrass 11-9206-4

TYPE

Suspension

STANDARD

OPTIONAL

2400K.

TRANSFORMER/DRIVER

DIMMING

CLASSIFICATION

UL IP20

ENERGY LABEL

YEAR OF DESIGN 2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887

> info@quasar.nl www.quasar.nl