Product data sheet

Date: August 31st 2025

QUASAR

TYPE.NR 11-9206-1 11-9206-2 11-9206-4



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIM	ENSIONS	LIGHTSOURCE	FINISH	
L	60 cm 23.6 inch	232x led, 12V/0.6W,	Nickel	(
Н	120 cm 47.2 inch	2800K, 12630 LM, CRI>95	Brass	1
W	60 cm 23.6 inch		Blackbrass	1
		INCLUDED		
CAN	IOPY	Yes		
L	25 cm 9.8 inch			
Н	6 cm 2.4 inch			
W	25 cm 9.8 inch			
		4 20 65x125x65cm		
CAE	BLELENGTH			

TYPE	Suspension
STANDARD	
OPTIONAL	2400K.
TRANSFORMER/DRIVER	
DIMMING	
CLASSIFICATION	UL IP20
ENERGY LABEL	
YEAR OF DESIGN	2019

Up to 200 cm 78 inch

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 info@quasar.nl www.quasar.nl