Product data sheet

Date: December 15th 2025


QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



280 cm110.2 inch 125 cm 49.2 inch W 130 cm 51.2 inch

CANOPY

59.5 cm 23.4 inch 10 cm 3.9 inch 37 cm 14.6 inch

CABLELENGTH Up to 200 cm 78 inch

1017x led. 12V/0.6W. 2800K, 30510 LM, CRI>95

INCLUDED

Yes

KG KG 200 290x140x150cm FINISH

Nickel

Blackbrass

TYPE.NR 11-9204-1

11-9204-2 11-9204-4

TYPE Suspension

STANDARD

2400K. OPTIONAL

TRANSFORMER/DRIVER Meanwell HLG602

DIMMING 0-10V

UL no CLASSIFICATION

IP20 yes

ENERGY LABEL

YEAR OF DESIGN 2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 info@quasar.nl www.quasar.nl