

Product data sheet

Date: March 4th 2026

QUASAR



POLLUX SUSPENSION by Jan

Pauwels

Pollux looks structured but still harmonious. Modular placed LED circuit boards and tiny metal rods are the only two basic elements of this light fixture. They give the lamp its structure and shape. The shape is totally irregular and asymmetrical. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards.



DIMENSIONS

L 60 cm 23.6 inch
H 120 cm 47.2 inch
W 60 cm 23.6 inch

CANOPY

L 25 cm 9.8 inch
H 6 cm 2.4 inch
W 25 cm 9.8 inch

CABLELENGTH

Up to 200 cm 78 inch

LIGHTSOURCE

232x led, 12V/0.6W,
2800K, 12630 LM, CRI>95

INCLUDED

Yes



FINISH

Nickel  11-9206-1
Brass  11-9206-2
Blackbrass  11-9206-4

TYPE.NR

TYPE Suspension

STANDARD

OPTIONAL 2400K.

TRANSFORMER/DRIVER Meanwell HLG604

DIMMING 0-10V

CLASSIFICATION UL no
IP20 yes

ENERGY LABEL

YEAR OF DESIGN 2019

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands

T. +31-(0)183-447887

info@quasar.nl www.quasar.nl